





LED Slim Downlight EcoMax III Dim

Technical Specifications	
CRI	80
Colour Consistency (SDCM)	≤6
Dimmable	Yes
Housing Colour	White
IP	IP20
IK	IK02
Driver integrated (Yes/No)	No
Glow wire test	650°C
Driver failure rate	1% at 5000h
Weight (pc/kg)	0.144/0.203/0.303/0.303
	0.157/0.238/0.353/0.353

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC / DC	AC

Mechanical Properties	
Housing Material	PC
Optical Material	PC

Application Conditions	
Operating Temperature	-15-45°C
Application Temperature	25°C
Storage Environment	-25-50°C



Features

- High Lumen Output
- Long lifespan
- Easy to Repair
- High Quality Dimming

Benefits

- Up to 50% energy saving compared to conventional downlight
- Lasts 3 times longer than conventional downlight , up to 30000hrs lifetime
- Independent driver can be replaced by professionals
- All versions available in different light colour and with Triac dimming

Application

Home, Shopping Mall, School, Retail, Hotel, Office


Specification

Item Code	Item Description	Power (W)	Power Factor	Lumen (lm)	Efficacy (lm/W)	Input Current (mA)	Lifetime (L70B50)	MOQ (pcs)
540001014810	LEDDownlight Rc-ES III R100-6W-Dim-3000-WH	6	0.9	450	75	60	30000	600
540001014910	LEDDownlight Rc-ESIII R100-6W-Dim-4000-WH	6	0.9	480	80	60	30000	600
540001014610	LEDDownlight Rc-ESIII R100-6W-Dim-6500-WH	6	0.9	480	80	60	30000	600
540001013410	LEDDownlight Rc-ESIII R150-12W-Dim-3000-WH	12	0.9	900	75	105	30000	600
540001013710	LEDDownlight Rc-ESIII R150-12W-Dim-4000-WH	12	0.9	960	80	105	30000	600
540001013210	LEDDownlight Rc-ESIII R150-12W-Dim-6500-WH	12	0.9	960	80	105	30000	600
540001014310	LEDDownlight Rc-ESIII R200-18W-Dim-3000-WH	18	0.9	1350	75	150	30000	600
540001013610	LEDDownlight Rc-ESIII R200-18W-Dim-4000-WH	18	0.9	1440	80	150	30000	600
540001013310	LEDDownlight Rc-ESIII R200-18W-Dim-6500-WH	18	0.9	1440	80	150	30000	600
540001013810	LEDDownlight Rc-ESIII R200-24W-Dim-3000-WH	24	0.9	1800	75	180	30000	600
540001013910	LEDDownlight Rc-ESIII R200-24W-Dim-4000-WH	24	0.9	1920	80	180	30000	600
540001014210	LEDDownlight Rc-ESIII R200-24W-Dim-6500-WH	24	0.9	1920	80	180	30000	600
540001013510	LEDDownlight Rc-ESIII S100-6W-Dim-3000-WH	6	0.9	450	75	60	30000	600
540001014510	LEDDownlight Rc-ESIII S100-6W-Dim-4000-WH	6	0.9	480	80	60	30000	600
540001014110	LEDDownlight Rc-ESIII S100-6W-Dim-6500-WH	6	0.9	480	80	60	30000	600
540001014410	LEDDownlight Rc-ESIII S150-12W-Dim-3000-WH	12	0.9	900	75	105	30000	600
540001014010	LEDDownlight Rc-ESIII S150-12W-Dim-4000-WH	12	0.9	960	80	105	30000	600
540001013110	LEDDownlight Rc-ESIII S150-12W-Dim-6500-WH	12	0.9	960	80	105	30000	600
540001015010	LEDDownlight Rc-ESIII S200-18W-Dim-3000-WH	18	0.9	1350	75	150	30000	600
540001014710	LEDDownlight Rc-ESIII S200-18W-Dim-4000-WH	18	0.9	1440	80	150	30000	600
540001015210	LEDDownlight Rc-ESIII S200-18W-Dim-6500-WH	18	0.9	1440	80	150	30000	600
540001015410	LEDDownlight Rc-ESIII S200-24W-Dim-3000-WH	24	0.9	1800	75	180	30000	600
540001015110	LEDDownlight Rc-ESIII S200-24W-Dim-4000-WH	24	0.9	1920	80	180	30000	600
540001015310	LEDDownlight Rc-ESIII S200-24W-Dim-6500-WH	24	0.9	1920	80	180	30000	600

Packaging Information

Item		Single Box(1pc/box)		Packaging Unit		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/unit)
540001014810	LEDDownlight Rc-ES III R100-6W-Dim-3000-WH	144*144*44	0.208	445*235*305	6.24	30
540001014910	LEDDownlight Rc-ESIII R100-6W-Dim-4000-WH	144*144*44	0.208	445*235*305	6.24	30
540001014610	LEDDownlight Rc-ESIII R100-6W-Dim-6500-WH	144*144*44	0.208	445*235*305	6.24	30
540001013410	LEDDownlight Rc-ESIII R150-12W-Dim-3000-WH	189*166*44	0.294	390*235*350	5.88	20
540001013710	LEDDownlight Rc-ESIII R150-12W-Dim-4000-WH	189*166*44	0.294	390*235*350	5.88	20
540001013210	LEDDownlight Rc-ESIII R150-12W-Dim-6500-WH	189*166*44	0.294	390*235*350	5.88	20
540001014310	LEDDownlight Rc-ESIII R200-18W-Dim-3000-WH	240*216*44	0.423	495*235*235	4.23	10
540001013610	LEDDownlight Rc-ESIII R200-18W-Dim-4000-WH	240*216*44	0.423	495*235*235	4.23	10
540001013310	LEDDownlight Rc-ESIII R200-18W-Dim-6500-WH	240*216*44	0.423	495*235*235	4.23	10
540001013810	LEDDownlight Rc-ESIII R200-24W-Dim-3000-WH	240*216*44	0.423	495*235*235	4.23	10
540001013910	LEDDownlight Rc-ESIII R200-24W-Dim-4000-WH	240*216*44	0.423	495*235*235	4.23	10
540001014210	LEDDownlight Rc-ESIII R200-24W-Dim-6500-WH	240*216*44	0.423	495*235*235	4.23	10
540001013510	LEDDownlight Rc-ESIII S100-6W-Dim-3000-WH	144*144*44	0.221	445*235*305	6.63	30
540001014510	LEDDownlight Rc-ESIII S100-6W-Dim-4000-WH	144*144*44	0.221	445*235*305	6.63	30
540001014110	LEDDownlight Rc-ESIII S100-6W-Dim-6500-WH	144*144*44	0.221	445*235*305	6.63	30
540001014410	LEDDownlight Rc-ESIII S150-12W-Dim-3000-WH	189*184*44	0.337	390*235*385	6.74	20
540001014010	LEDDownlight Rc-ESIII S150-12W-Dim-4000-WH	189*184*44	0.337	390*235*385	6.74	20
540001013110	LEDDownlight Rc-ESIII S150-12W-Dim-6500-WH	189*184*44	0.337	390*235*385	6.74	20
540001015010	LEDDownlight Rc-ESIII S200-18W-Dim-3000-WH	240*234*44	0.495	495*235*250	4.95	10
540001014710	LEDDownlight Rc-ESIII S200-18W-Dim-4000-WH	240*234*44	0.495	495*235*250	4.95	10
540001015210	LEDDownlight Rc-ESIII S200-18W-Dim-6500-WH	240*234*44	0.495	495*235*250	4.95	10
540001015410	LEDDownlight Rc-ESIII S200-24W-Dim-3000-WH	240*234*44	0.495	495*235*250	4.95	10
540001015110	LEDDownlight Rc-ESIII S200-24W-Dim-4000-WH	240*234*44	0.495	495*235*250	4.95	10
540001015310	LEDDownlight Rc-ESIII S200-24W-Dim-6500-WH	240*234*44	0.495	495*235*250	4.95	10


Dimensional Drawing



Type	A(mm)	C(mm)
LED DL-RC-ESIII R100 6W Dim	Φ112	29
LED DL-RC-ESIII R150 12W Dim	Φ162	29
LED DL-RC-ESIII R200 18W Dim	Φ212	29
LED DL-RC-ESIII R200 24W Dim	Φ212	29

Type	A(mm)	B(mm)	H(mm)
LED DL-RC-ESIII S100 6W Dim	112	112	29
LED DL-RC-ESIII S150 12W Dim	162	162	29
LED DL-RC-ESIII S200 18W Dim	212	212	29
LED DL-RC-ESIII S200 24W Dim	212	212	29

Photometric Data



6W/12W/18W/24W

Dimmer List

Manufacturer	Model
PHILIPS	SED-200A
MK	EX8501
MK	SX8501
CLIPSAL	S/I/E32
Schneider	KB32V500
STEP	E033N
Panasonic	WEG 57813
Legrand	281084
Legrand	617030





LED Slim Downlight EcoMax III HPF

Features

- High efficacy
- High lumen output
- Look good
- High PF
- Long lifespan

Benefits

- Up to 50% energy saving compared to conventional downlight
- Lasts 3 times longer than conventional downlight, up to30000hrs lifetime
- A slim, stylish body gives this luminaire a modern aesthetic that brings beauty to any space

Application

Home · Shopping Mall · School · Conference Room · Hospital

Specification

Item Code	Item Description	Power (W)	Power Factor	Lumen (lm)	Efficacy (lm/W)	Input Current (mA)	Lifetime (L70B50)	MOQ (pcs)
540001035610	LEDDownlight Rc-HPF ESIII R100-6W-3000-WH	6	0.9	480	80	29	30000	600
540001034810	LEDDownlight Rc-HPF ESIII R100-6W-4000-WH	6	0.9	480	80	29	30000	600
540001034910	LEDDownlight Rc-HPF ESIII R100-6W-6500-WH	6	0.9	480	80	29	30000	600
540001034410	LEDDownlight Rc-HPF ESIII R150-12W-3000-W	12	0.9	960	80	58	30000	600
540001034510	LEDDownlight Rc-HPF ESIII R150-12W-4000-W	12	0.9	960	80	58	30000	600
540001033910	LEDDownlight Rc-HPF ESIII R150-12W-6500-W	12	0.9	960	80	58	30000	600
540001034610	LEDDownlight Rc-HPF ESIII R200-18W-3000-W	18	0.9	1440	80	80	30000	600
540001036110	LEDDownlight Rc-HPF ESIII R200-18W-4000-W	18	0.9	1440	80	80	30000	600
540001035210	LEDDownlight Rc-HPF ESIII R200-18W-6500-W	18	0.9	1440	80	80	30000	600
540001035710	LEDDownlight Rc-HPF ESIII R200-24W-3000-W	24	0.9	1920	80	108	30000	600
540001034310	LEDDownlight Rc-HPF ESIII R200-24W-4000-W	24	0.9	1920	80	108	30000	600
540001035310	LEDDownlight Rc-HPF ESIII R200-24W-6500-W	24	0.9	1920	80	108	30000	600
540001035010	LEDDownlight Rc-HPF ESIII S100-6W-3000-WH	6	0.9	480	80	29	30000	600
540001035510	LEDDownlight Rc-HPF ESIII S100-6W-4000-WH	6	0.9	480	80	29	30000	600
540001035110	LEDDownlight Rc-HPF ESIII S100-6W-6500-WH	6	0.9	480	80	29	30000	600
540001035810	LEDDownlight Rc-HPF ESIII S150-12W-3000-W	12	0.9	960	80	58	30000	600
540001036210	LEDDownlight Rc-HPF ESIII S150-12W-4000-W	12	0.9	960	80	58	30000	600
540001036010	LEDDownlight Rc-HPF ESIII S150-12W-6500-W	12	0.9	960	80	58	30000	600
540001034110	LEDDownlight Rc-HPF ESIII S200-18W-3000-W	18	0.9	1440	80	80	30000	600
540001034210	LEDDownlight Rc-HPF ESIII S200-18W-4000-W	18	0.9	1440	80	80	30000	600
540001034710	LEDDownlight Rc-HPF ESIII S200-18W-6500-W	18	0.9	1440	80	80	30000	600
540001034010	LEDDownlight Rc-HPF ESIII S200-24W-3000-W	24	0.9	1920	80	108	30000	600
540001035910	LEDDownlight Rc-HPF ESIII S200-24W-4000-W	24	0.9	1920	80	108	30000	600
540001035410	LEDDownlight Rc-HPF ESIII S200-24W-6500-W	24	0.9	1920	80	108	30000	600


Technical Specifications	
CRI	80
Colour Consistency (SDCM)	⩽6
Dimmable	No
Housing Colour	White
IP	IP20
IK	IK02
Driver integrated (Yes/No)	Yes
Glow wire test	650°C
Driver failure rate	1% at 5000h
Weight (pc/kg)	0.12/0.18/0.275/0.135 0.21/0.325

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Mechanical Properties	
Optical Material	PC
Housing Material	PC

Application Conditions	
Operating Temperature	-10~45°C
Application Temperature	25°C
Storage Environment	-25~50°C


CE CB




Packaging Information

Item		Single Box(1pc/box)		Outer box		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/CTN)
540001035610	LEDDownlight Rc-HPF ESIII R100-6W-3000-WH	144*44*129	0.186	445*235*275	5.58	30
540001034810	LEDDownlight Rc-HPF ESIII R100-6W-4000-WH	144*44*129	0.186	445*235*275	5.58	30
540001034910	LEDDownlight Rc-HPF ESIII R100-6W-6500-WH	144*44*129	0.186	445*235*275	5.58	30
540001034410	LEDDownlight Rc-HPF ESIII R150-12W-3000-W	189*44*166	0.268	390*235*350	5.36	20
540001034510	LEDDownlight Rc-HPF ESIII R150-12W-4000-W	189*44*166	0.268	390*235*350	5.36	20
540001033910	LEDDownlight Rc-HPF ESIII R150-12W-6500-W	189*44*166	0.268	390*235*350	5.36	20
540001034610	LEDDownlight Rc-HPF ESIII R200-18W-3000-W	240*44*216	0.41	495*235*235	4.1	10
540001036110	LEDDownlight Rc-HPF ESIII R200-18W-4000-W	240*44*216	0.41	495*235*235	4.1	10
540001035210	LEDDownlight Rc-HPF ESIII R200-18W-6500-W	240*44*216	0.41	495*235*235	4.1	10
540001035710	LEDDownlight Rc-HPF ESIII R200-24W-3000-W	240*44*216	0.41	495*235*235	4.1	10
540001034310	LEDDownlight Rc-HPF ESIII R200-24W-4000-W	240*44*216	0.41	495*235*235	4.1	10
540001035310	LEDDownlight Rc-HPF ESIII R200-24W-6500-W	240*44*216	0.41	495*235*235	4.1	10
540001035010	LEDDownlight Rc-HPF ESIII S100-6W-3000-WH	144*44*144	0.202	445*235*305	6.06	30
540001035510	LEDDownlight Rc-HPF ESIII S100-6W-4000-WH	144*44*144	0.202	445*235*305	6.06	30
540001035110	LEDDownlight Rc-HPF ESIII S100-6W-6500-WH	144*44*144	0.202	445*235*305	6.06	30
540001035810	LEDDownlight Rc-HPF ESIII S150-12W-3000-W	189*44*184	0.309	390*235*385	6.18	20
540001036210	LEDDownlight Rc-HPF ESIII S150-12W-4000-W	189*44*184	0.309	390*235*385	6.18	20
540001036010	LEDDownlight Rc-HPF ESIII S150-12W-6500-W	189*44*184	0.309	390*235*385	6.18	20
540001034110	LEDDownlight Rc-HPF ESIII S200-18W-3000-W	240*44*234	0.47	495*235*250	4.7	10
540001034210	LEDDownlight Rc-HPF ESIII S200-18W-4000-W	240*44*234	0.47	495*235*250	4.7	10
540001034710	LEDDownlight Rc-HPF ESIII S200-18W-6500-W	240*44*234	0.47	495*235*250	4.7	10
540001034010	LEDDownlight Rc-HPF ESIII S200-24W-3000-W	240*44*234	0.47	495*235*250	4.7	10
540001035910	LEDDownlight Rc-HPF ESIII S200-24W-4000-W	240*44*234	0.47	495*235*250	4.7	10
540001035410	LEDDownlight Rc-HPF ESIII S200-24W-6500-W	240*44*234	0.47	495*235*250	4.7	10


Dimensional Drawing




6W




12W




18/24W



6W




12W




18/24W


Cut-out Drawing




Φ100
6W




Φ150
12W




Φ200
18W




Φ200
24W




100X100
6W



150X150
12W




200X200
18W



200X200
24W

Photometric Data



6W/12W/18W/24W





LED Slim Downlight EcoMax III

Features

- High lumen output
- Long lifespan
- Easy to repair
- Looking good

Benefits

- Up to 50% energy saving compared to conventional downlight
- Lasts 3 times longer than conventional downlight, upto30000hrs lifetime
- Independent driver can be replaced by professionals
- A slim, stylish body gives this luminaire a modern aesthetic that brings beauty to any space

Application



Home



Shopping Mall



School



Conference Room



Hospital

Specification

Item Code	Item Description	Power (W)	Power Factor	Lumen (lm)	Efficacy (lm/W)	Input Current (mA)	CRI	CTT (K)	Lifetime (L70B50)	MOQ (pcs)
140062536	LEDDownlightRc-ESIII R100-6W-3000-WH-NV	6	0.5	450	75	60	>80	3000	30000	600
140062537	LEDDownlightRc-ESIII R100-6W-4000-WH-NV	6	0.5	480	80	60	>80	4000	30000	600
140062538	LEDDownlightRc-ESIII R100-6W-6500-WH-NV	6	0.5	480	80	60	>80	6500	30000	600
140062539	LEDDownlightRc-ESIII R150-12W-3000-WH-NV	12	0.5	900	75	105	>80	3000	30000	600
140062540	LEDDownlightRc-ESIII R150-12W-4000-WH-NV	12	0.5	960	80	105	>80	4000	30000	600
140062541	LEDDownlightRc-ESIII R150-12W-6500-WH-NV	12	0_5	960	80	105	>80	6500	30000	600
140062542	LEDDownlightRc-ESIII R200-18W-3000-WH-NV	18	0.5	1350	75	150	>80	3000	30000	600
140062543	LEDDownlightRc-ESIII R200-18W-4000-WH-NV	18	0.5	1440	80	150	>80	4000	30000	600
140062544	LEDDownlightRc-ESIII R200-18W-6500-WH-NV	18	0.5	1440	80	150	>80	6500	30000	600
140062545	LEDDownlightRc-ESIII R200-24W-3000-WH-NV	24	0.5	1800	75	180	>80	3000	30000	600
140062546	LEDDownlightRc-ESIII R200-24W-4000-WH-NV	24	0.5	1920	80	180	>80	4000	30000	600
140062547	LEDDownlightRc-ESIII R200-24W-6500-WH-NV	24	0.5	1920	80	180	>80	6500	30000	600
140062548	LEDDownlightRc-ESIII S100-6W-3000-WH-NV	6	0.5	450	75	60	>80	3000	30000	600
140062549	LEDDownlightRc-ESIII S100-6W-4000-WH-NV	6	0.5	480	80	60	>80	4000	30000	600
140062550	LEDDownlightRc-ESIII S100-6W-6500-WH-NV	6	0.5	480	80	60	>80	6500	30000	600
140062551	LEDDownlightRc-ESIII S150-12W-3000-WH-NV	12	0.5	900	75	105	>80	3000	30000	600
140062552	LEDDownlightRc-ESIII S150-12W-4000-WH-NV	12	0.5	960	80	105	>80	4000	30000	600
140062553	LEDDownlightRc-ESIII S150-12W-6500-WH-NV	12	0.5	960	80	105	>80	6500	30000	600
140062554	LEDDownlightRc-ESIII S200-18W-3000-WH-NV	18	0.5	1350	75	150	>80	3000	30000	600
140062555	LEDDownlightRc-ESIII S200-18W-4000-WH-NV	18	0.5	1440	80	150	>80	4000	30000	600
140062556	LEDDownlightRc-ESIII S200-18W-6500-WH-NV	18	0.5	1440	80	150	>80	6500	30000	600
140062557	LEDDownlightRc-ESIII S200-24W-3000-WH-NV	24	0.5	1800	75	180	>80	3000	30000	600
140062558	LEDDownlightRc-ESIII S200-24W-4000-WH-NV	24	0.5	1920	80	180	>80	4000	30000	600
140062559	LEDDownlightRc-ESIII S200-24W-6500-WH-NV	24	0.5	1920	80	180	>80	6500	30000	600


Technical Specifications	
On/Off Cycles	50000
Color Consistency (SDCM)	≤6
Dimmable	No
Beam Angle (°)	120
Finishing Color	White
ip	IP20
Driver Integrated (Yes/No)	NO
Glow Wire Test	650°C
Driver Failure Rate	1% at 50000h
Weight (kg/pc)	0.12/0.18/0.275/0.135
	0.21/0.325

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Mechanical Properties	
Optical Material	PC
Housing Material	PC

Application Conditions	
Operating Temperature	-10-40°C
Application Temperature	25°C
Storage Environment	-25-50°C


CE CB




Packaging Information

Item		Single Box(1pc/box)		Outer box		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/CTN)
140062536	LEDDownlightRc-ESIII R100-6W-3000-WH-NV	144*44*129	0.19	445*235*275	5.58	30
140062537	LEDDownlightRc-ESIII R100-6W-4000-WH-NV	144*44*129	0.19	445*235*275	5.58	30
140062538	LEDDownlightRc-ESIII R100-6W-6500-WH-NV	144*44*129	0.19	445*235*275	5.58	30
140062539	LEDDownlightRc-ESIII R150-12W-3000-WH-NV	189*44*166	0.27	390*235*350	5.36	20
140062540	LEDDownlightRc-ESIII R150-12W-4000-WH-NV	189*44*166	0.27	390*235*350	5.36	20
140062541	LEDDownlightRc-ESIII R150-12W-6500-WH-NV	189*44*166	0.27	390*235*350	5.36	20
140062542	LEDDownlightRc-ESIII R200-18W-3000-WH-NV	240*44*216	0.41	495*235*235	4.1	10
140062543	LEDDownlightRc-ESIII R200-18W-4000-WH-NV	240*44*216	0.41	495*235*235	4.1	10
140062544	LEDDownlightRc-ESIII R200-18W-6500-WH-NV	240*44*216	0.41	495*235*235	4.1	10
140062545	LEDDownlightRc-ESIII R200-24W-3000-WH-NV	240*44*216	0.41	495*235*235	4.1	10
140062546	LEDDownlightRc-ESIII R200-24W-4000-WH-NV	240*44*216	0.41	495*235*235	4.1	10
140062547	LEDDownlightRc-ESIII R200-24W-6500-WH-NV	240*44*216	0.41	495*235*235	4.1	10
140062548	LEDDownlightRc-ESIII S100-6W-3000-WH-NV	144*44*144	0.20	445*235*305	6.06	30
140062549	LEDDownlightRc-ESIII S100-6W-4000-WH-NV	144*44*144	0.20	445*235*305	6.06	30
140062550	LEDDownlightRc-ESIII S100-6W-6500-WH-NV	144*44*144	0.20	445*235*305	6.06	30
140062551	LEDDownlightRc-ESIII S150-12W-3000-WH-NV	189*44*184	0.31	390*235*385	6.18	20
140062552	LEDDownlightRc-ESIII S150-12W-4000-WH-NV	189*44*184	0.31	390*235*385	6.18	20
140062553	LEDDownlightRc-ESIII S150-12W-6500-WH-NV	189*44*184	0.31	390*235*385	6.18	20
140062554	LEDDownlightRc-ESIII S200-18W-3000-WH-NV	240*44*234	0.47	495*235*250	4.7	10
140062555	LEDDownlightRc-ESIII S200-18W-4000-WH-NV	240*44*234	0.47	495*235*250	4.7	10
140062556	LEDDownlightRc-ESIII S200-18W-6500-WH-NV	240*44*234	0.47	495*235*250	4.7	10
140062557	LEDDownlightRc-ESIII S200-24W-3000-WH-NV	240*44*234	0.47	495*235*250	4.7	10
140062558	LEDDownlightRc-ESIII S200-24W-4000-WH-NV	240*44*234	0.47	495*235*250	4.7	10
140062559	LEDDownlightRc-ESIII S200-24W-6500-WH-NV	240*44*234	0.47	495*235*250	4.7	10


Dimensional Drawing




6W




12W




18/24W



6W



12W



18/24W